



BATTERY KIT

DISPENSERS

EN. Portable diesel transfer unit. Self-priming electric vane pump run by a 12V or 24 V DC electric motor. Cast iron body. Fixed brush motor with permanent magnet stator. Suction capacity up to 2 metres. Terminal board with switches and fuses to protect against overload. 2 metre cables with clips for battery connection. 4 meter fuel pipe, diameter 3/4". Aluminium manual nozzle. Bottom suction filter.

RU. Переносной узел для перекачивания дизельного топлива. Самовсасывающий крыльчатый электронасос с двигателем 12 или 24 В постоянного тока. Чугунный корпус. Щеточный двигатель со статором с постоянными магнитами. Высота всасывания до 2 метров. Клеммная колодка с выключателем и предохранителем для защиты от перегрузок. Кабели длиной 2 метра с зажимами для соединения с аккумулятором. Труба длиной 4 метра для топлива, диаметр 3/4". Ручной пистолет из алюминия. Донный фильтр для всасывающей трубы.

DE. Tragbares Dieselförderaggregat. Selbstansaugende, elektrische Flügelzellenpumpe mit 12V- oder 24V-Gleichstrommotor. Pumpenkörper aus Gusseisen. Bürstenmotor mit Permanentmagnet-Stator. Saugleistung bis zu 2 m. Klemmleiste mit Schalter und Schmelzsicherung zum Schutz gegen Überlasten. 2-m-Kabel mit Klemmen zur Verbindung mit der Batterie. 4-m-Kraftstoffschlauch, Durchmesser 3/4". Manuelle Abgabepistole aus Aluminium. Bodenfilter für den Saugschlauch.

PERFORMANCE

- Flow rate up to 50 l/min
- 12 - 24 V DC operation
- Duty cycle 30 min.

- Расход до 50 л/мин
- Функционирование от источника постоянного тока 12 - 24 В
- Рабочий цикл 30 мин.

- Durchflussmenge bis 50 l/Min.
- Stromversorgung 12 - 24 V DC
- Arbeitszyklus 30 Min.



PRODUCTS' RANGE WEIGHT AND PACKAGING

Code	Weight		Packaging		
	kg	lbs	mm	inch	pcs/box
BATTERY KIT 3000					
F0022500C	7,8	17,3	300x300x180	18,8x11,8x7,1	1
F0022600C	7,8	17,3	300x300x180	18,8x11,8x7,1	1
F00225410	7,8	17,3	300x300x180	18,8x11,8x7,1	1
F00226380	7,8	17,3	300x300x180	18,8x11,8x7,1	1
BATTERY KIT PANTHER					
F0034003B	7,8	17,3	300x300x180	18,8x11,8x7,1	1
F0034103C	7,8	17,3	300x300x180	18,8x11,8x7,1	1
F0034006B	12,5	27,6	357x357x275	14,1x14,1x10,8	1
F00341220	13	28,7	357x357x275	14,1x14,1x10,8	1
F0034106C	12,5	27,6	357x357x275	14,1x14,1x10,8	1
BATTERY KIT BIPUMP					
F00363280	18	39,7	480x370x265	18,9x14,6x10,4	1
CARRY 3000					
F0022300C	7,8	17,3	300x300x180	18,8x11,8x7,1	1
F0022400C	7,8	17,3	300x300x180	18,8x11,8x7,1	1



Flow-rate

up to
50 l/min
(up to 10 gpm)



BATTERY KIT 3000



BATTERY KIT 3000 INLINE



BATTERY KIT PANTHER



BATTERY KIT OIL



BATTERY KIT BIPUMP

Delivery hose 6 m
Cable lenght 4 m
Automatic nozzle

FEATURES

ON REQUEST




Handle



On/Off switch



Automatic nozzle



DRUM KIT

PRODUCTS' RANGE TECHNICAL DATA

Code	Description	Fluids type	Flow-rate		Voltage			Fuses capacity	Pump mod.	Duty cycle min.	Nozzle type	Hose		Foot filter
			l/min	gpm	AC V/Hz DC Volt	Power Watt	Amp. max.					length	Ø	
BATTERY KIT 3000														
F0022500C	BATTERY KIT 3000 12V	D	50	13	12	220	22	25	Carry 3000	30	Man.	4 m	3/4"	YES
F0022600C	BATTERY KIT 3000 24V	D	50	13	24	310	13	15	Carry 3000	30	Man.	4 m	3/4"	YES
F00225410	BATTERY KIT 3000 INLINE 12V	D	50	13	12	220	22	25	Carry 3000	30	Man.	4 m	3/4"	YES
F00226380	BATTERY KIT 3000 INLINE 24V	D	50	13	24	310	13	15	Carry 3000	30	Man.	4 m	3/4"	YES
BATTERY KIT PANTHER														
F0034003B	BATTERY KIT Panther 12V	D	56	15	12	300	35	40	Panther DC	30	Man.	4 m	3/4"	YES
F0034103C	BATTERY KIT Panther 12-24V	D	35/70	9/18	24/12	420/150	25/16	30/30	Panther DC	30	Man.	4 m	3/4"	YES
F0034006B	BATTERY KIT Panther 12V	D	56	15	12	420	35	-	Panther DC	30	Man.	5 m	3/4"	YES
F00341220	BATTERY KIT Panther 12-24V	D	35/70	9/18	12/24	600/200	25/16	-	Panther DC	30	Aut.	5 m	3/4"	YES
F0034106C	BATTERY KIT Panther 12-24V	D	35/70	9/18	12/24	600/200	25/16	-	Panther DC	30	Man.	5 m	3/4"	YES
BATTERY KIT BIPUMP														
F00363280	BATTERY KIT Bipump 12V	D	80	21	12	300	22	-	Bipump DC	30	Aut.	6 m	1"	YES
BATTERY KIT OIL														
F00309060	Battery Viscomat/12 V	O	10	3	12	300	22	-	Viscomat DC	30	Man.	4 m	3/4"	YES
F00310070	Battery Viscomat/24 V	O	10	3	24	300	18	-	Viscomat DC	30	Man.	4 m	3/4"	YES

Upon request it is available with different voltages and 60 Hz frequency